## **DEFWB** Dielectric Flange






## Features

- Steel side weld end x bronze side solder end
- Flanged to PN16 or ANSI 150
- Bronze side solder end
- Steel side welded end

## **Technical data**

Max. pressure:	17.2 Bar (250psi)			
Max. temp:	120°C (248°F)			



Model	Steel Side (	Connection	Copper Side Connection		Α		В		Kgs
meder					in	mm	in	mm	
DEF-WB-1	2 1/2"	Weld	67mm (2 5/8")	Solder	7 1/4	184	3 1/2	89	5.4
DEF-WB-2	3"	Weld	80mm (3 1/8")	Solder	7 3/4	197	3 3/4	95	6.4
DEF-WB-3	4"	Weld	105mm (4 1/8")	Solder	8 3/4	222	4 3/8	111	13.6
DEF-WB-4	5"	Weld	130mm (5 1/8")	Solder	9 3/4	248	5 1/4	133	16.8
DEF-WB-5	6"	Weld	155mm (6 1/8")	Solder	11 1/4	285	6	153	19.2
DEF-WB-6	8"	Weld	206mm (8 1/8")	Solder	13 3/8	340	7 3/4	196	27.3

Part Name	Materials	Part Name	Materials
Steel Flange	Galvanised Steel	Bolt Insulators	ABS
Bolts	Galvanised Steel	Gasket	Nylon reinforced EPDM
Washer	Galvanised Steel	Tail Piece	Bronze
Nuts	Galvanised Steel	Tail Piece Insulator	ABS

V1. Dimensions in mm

This data sheet is designed as a guide and should not be regarded as wholly accurate in every detail. We reserve the right to amend the specification of any product without notice.