




HB Hexagon Backnut




Features

- Made from CF8M (316) Stainless Steel material and conform to ISO 4144 standard.
- Threads are to ISO 7-1 (DIN2999) BSPP Female, BSPT Male.
- Material certificates available on request.
- Tested & inspected prior to despatch.
- 12 month warranty from date of installation.
- Manufactured in accordance with ISO9001:2015 quality system.



DN	A	B	Kgs
1/8"	6.00	18.00	0.010
1/4"	6.14	20.96	0.011
3/8"	7.16	26.00	0.021
1/2"	8.00	30.99	0.030
3/4"	9.20	35.00	0.036
1"	10.00	44.94	0.065
1 1/4"	11.20	54.00	0.103
1 1/2"	11.88	58.85	0.112
2"	13.20	74.00	0.203
2 1/2"	15.96	93.50	0.401
3"	19.10	106.20	0.500
4"	23.22	133.90	0.924



Temperature (°C)	Non-shock maximum working pressure (bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

- NOTE 1 Pressure for intermediate temperatures may be determined by the interpolation method.
- NOTE 2 Temperatures indicated are those of internal fluid.
- NOTE 3 Piping loads, stresses and moments are not taken into account.